



CERTIFICATO N.58200

Revisione N°2

Data 06.11.2018

Pag. 1 di 1

SCHEDA TECNICA

SBLOCCANTE LUBRIFICANTE SPRAY AR1046

1. Area of use

Unblocking and antioxidant agent for mechanical parts moving and fixed.

2. Description

This product, thanks to its particular formula, instantly unblocks all metal parts like chains, bolts, joints encrusted with rust and/or oxidation. It performs a protective and preventive action, leaving a slick film.

3. Technical Characteristics

- ASPECT: aerosol packaging;
- COLOR: trasparente;
- DENSITY SPRAY: 0.675 kg / l (+/- 0.05);
- PROPELLENT: G.P.L. (Propane / Butane),
- FLAMMABILITY: Extremely flammable;
- STORAGE: temperatures between + 10 ° C and + 30 ° C; fresh local ed ventilated; avoid the accumulation of electrostatic charges.
- PACKAGING: 400ml x12pz
- EXPIRY: 3 years from production date

4. Use

Spray the product directly on the interesting parties keeping the can upright. If necessary insert the tube into the spray nozzle. Wait some instant.

Read and observe the warnings reported back on the container's label.

For the relative information of the manipulation, transport, etc..., make reference to the Safety Data Sheet of relative emergency to the product in issue.

The information contained in the present documentation, refer to the knowledges of the product to the date above indicated.

PREXISO SRL VIA SANTA CRISTINA 18 - 10036 Settimo T.se (TO) ITALIA

Tel . +39.011/19876454

WWW.PREXISOITALIA.IT E-mail: INFO@PREXISOITALIA.IT

P.IVA IT 11623200018 REA TO-1228124



CERTIFICATO N.58200

Revisione	N°2
Data 06.11.2018	
Pag. 2 di 1	

Considering however numerous possible employs and eventual interferences from elements which do not depend from the producer, it is not possible to assume some responsibility about the indications written on the back.